

ENABLE SIGNALS MUST BE INVERTED USING THE ACORN SETUP WIZARD.  
DYN4 SERVO DRIVE MUST HAVE COMMAND INPUT MODE SET TO "PULSE/DIR"

Title: ACORN\_rev4, DMM DYN4, DMM CABLE # CA-CUACRN-M4-05

Date: 210420

Ver: 3


Drawn by: CEM

Filename: S14989.DWG

Sheet 1 of 1

How to tell the difference between Acorn\_rev2, Acorn\_rev3 and Acorn\_rev4  
Acorn\_rev2 has FIXED green screw terminal blocks  
Acorn\_rev3 has REMOVABLE green screw terminal blocks  
Acorn\_rev4 has LED indicators for the Inputs and Outputs

ACORN I/O	1	2	3	4
INPUTS	HomeAll	LimitAll		
OUTPUTS	NoFaultout			
ACORN I/O	5	6	7	8
INPUTS	DriveOK			EStopOK
OUTPUTS				



SEE DRIVE MANUAL FOR  
PROGRAMMING AND MOTOR  
AND POWER CONNECTIONS

E-STOP CIRCUITS ARE RED  
OPTIONAL CONNECTIONS ARE BLUE  
GROUNDS ARE GREEN  
110VAC IS VIOLET