












































SUGGESTED WIRE CURRENT CAPACITY STRANDED MTW OR EQUIVALENT
18 AWG - UP TO 6A
16 AWG - UP TO 8A
14 AWG - UP TO 15A
12 AWG - UP TO 20A
10 AWG - UP TO 30A
8 AWG - UP TO 40A
6 AWG - UP TO 60A
LIMIT SWITCH OPTIONS
ONE CABLE PER SWITCH
X- COMMON, BLACK
X+ LIMIT RED
X+ COMMON, BLACK
Y- LIMIT WHITE
Y- COMMON, BLACK
Y+ LIMIT RED
Y+ COMMON, BLACK
Z- LIMIT RED
Z- COMMON, BLACK
Z+ LIMIT RED
Z+ COMMON, BLACK
ONE CABLE PER AXIS
X- LIMIT WHITE
X- COMMON, BLACK
X+ LIMIT RED
X+ COMMON, GREEN
Y- LIMIT WHITE
Y- COMMON, BLACK
Y+ LIMIT RED
Y+ COMMON, GREEN
Z- LIMIT WHITE
Z- COMMON, BLACK
Z+ LIMIT RED
Z+ COMMON, GREEN
ONE CABLE X,Y AXIS
X- LIMIT WHITE
X- COMMON, BLACK
X+ LIMIT RED
X+ COMMON, GREEN
Y- LIMIT ORANGE
Y- COMMON, BROWN
Y+ LIMIT YELLOW
Y+ COMMON, BLUE
Z- LIMIT WHITE
Z- COMMON, BLACK
Z+ LIMIT RED
Z+ COMMON, GREEN
ONE CABLE Z AXIS
Z- LIMIT WHITE
Z- COMMON, BLACK
Z+ LIMIT RED
Z+ COMMON, GREEN
All limit switch cables minimum 22AWG shielded. All shields grounded
"NOTE" FUSE RATING DEPENDS ON SPINDLE HP
FUSE RATING LOCATION CIRCUIT
F1 15ATD B1 INCOMING SINGLE PHASE
F2 NOTE B1 INCOMING 3 PHASE
F3 NOTE B1 INCOMING 3 PHASE
F4 NOTE B1 INCOMING 3 PHASE